AMENDMENTS TO THE CLAIMS

List of Claims:

1. (Currently Amended) A wood-type golf club comprising a club shaft and a club head attached to an end of the club shaft, wherein

~~a club~~ the club length is in a range of from 43 to 48 inches,

~~a volume~~ the volume of the club head is in a range of not less than 250 cc, and

~~a torque~~ the torque T in degree of the club shaft ~~and a~~ and the gravity point distance L in mm between the gravity point of the club head and the center line of the club shaft satisfy the following conditions (1) and (2)

(1) $T \geq 0.143L-2.79$ and

(2) $T \leq 0.286L-7.14,$ wherein the torque T is defined as a twist angle in degree of the shaft measured at a position at 40 mm from said end of the shaft by applying a torque Tr of 13.9 kgf·m to this 40 mm position, while fixing a position of the shaft at 865 mm from said end.

2. (Currently Amended) ~~A wood-type~~ The wood-type golf club according to claim 1, wherein

4

the torque T and gravity point distance L satisfy said condition (1) and the following condition (3)

(3) $T \leq 0.286L - 7.89$.

3.   (Currently Amended)   ~~A wood-type~~ <u>The wood-type</u> golf club according to claim 1, wherein said gravity point distance L is in a range of from 33 to 41 mm.

4.   (Currently Amended)   ~~A wood-type~~ <u>The wood-type</u> golf club according to claim 1, wherein ~~said~~ <u>the</u> volume of the club head is in a range of from 270 to 500 cc.

5.   (Currently Amended)   ~~A wood-type~~ <u>The wood-type</u> golf club according to claim 1, wherein ~~said~~ <u>the</u> volume of the club head is in a range of from 300 to 500 cc.

6.   (Currently Amended)   ~~A wood-type~~ <u>The wood-type</u> golf club according to claim 1, wherein ~~said~~ <u>the</u> volume of the club head is in a range of from 320 to 480 cc.

7.   (Currently Amended)   A method of making a golf club, the golf club ~~comprising~~ <u>including</u> a club shaft and a club head attached to the end of the club shaft, the method comprising

measuring a torque T in degree of the club shaft,

measuring a gravity point distance L in mm between the gravity point of the club head and the center line of the club shaft,

~~examining~~ determining whether the torque T and gravity point distance L satisfy the following conditions (1) and (2)

(1) $T \geq 0.143L-2.79$ and

(2) $T \leq 0.286L-7.14$, and

assembling the club shaft and club head when their torque T and gravity point distance L satisfy ~~said~~ the conditions (1) and (2).

8. (Currently Amended) ~~A method~~ The method of making a golf club according to claim 7, which further comprises

making a club head which has a head volume in a range of not less than 250 cc and the gravity point distance L in a range of from 33 to 41 mm.

9. (Currently Amended) ~~A method~~ The method of making a golf club according to claim 7, which further comprises

making a club shaft which provides a club length in a range of from 43 to 48 inches.

10.   (New)   A method of making a golf club, the golf club including a club shaft and a club head attached to the end of the club shaft, the method comprising

providing a torque T in degree of the club shaft,

providing a gravity point distance L in mm between the gravity point of the club head and the center line of the club shaft,

determining whether the obtained torque T and gravity point distance L satisfy the following conditions (1) and (2)

(1) $T \geq 0.143L - 2.79$ and

(2) $T \leq 0.286L - 7.14$, and

assembling the club shaft and club head when their torque T and gravity point distance L satisfy the conditions (1) and (2).

11.   (New)   The method of claim 7, wherein the torque T and the gravity point distance L satisfy said condition (1) and the following condition (3)

(3) $T \leq 0.286L - 7.89$.

7